

Stute Violation Details CY 2021 - 2025TD

WAC Chapter Section	WAC Cited	WAC Text	2021	2022	2023	2024	2025	Totals
			Vios	Vios	Vios	Vios	Vios	
880-200	296-880-20005(1)	WAC 296-880-20005 Fall protection required at four feet or more. (1) Walking/working surfaces with unprotected sides or edges. Except as required in subsections (2) through (4) of this section.	23	42	62	49	6	182
	296-880-20005(1)(a)(ii)	WAC 296-880-20005 Fall protection required at four feet or more. (1) Walking/working surfaces with unprotected sides or edges. Except as required in subsections (2) through (4) of this section.		1	1	2		4
	296-880-20005(1)(a)(iii)	WAC 296-880-20005 Fall protection required at four feet or more. (1) Walking/working surfaces with unprotected sides or edges. Except as required in subsections (2) through (4) of this section.				1		1
	296-880-20005(2)(a)	WAC 296-880-20005 Fall protection required at four feet or more. (2) Guarding of ramps, runways, and inclined walkways. (a) Ramps, runways, and inclined walkways that are not designed to be used as ramps, runways, or inclined walkways.			2			2
	296-880-20005(3)(a)	WAC 296-880-20005 Fall protection required at four feet or more. (3) Holes. (a) The employer must protect employees from falling into or through holes four feet or more in diameter.		1	8	1	1	11
	296-880-20005(3)(b)	WAC 296-880-20005 Fall protection required at four feet or more. (3) Holes. (b) The employer must guard skylight holes and skylights. (i) Unprotected skylight holes must be guarded by a cover or other effective means.	2	1	5	1		9
	296-880-20005(4)	WAC 296-880-20005 Fall protection required at four feet or more. (4) Guarding of openings. The employer must ensure that each employee working on, at, above, or near openings is protected from falling.	3	7	18	16	1	45
	296-880-20005(6)	WAC 296-880-20005 Fall protection required at four feet or more. (6) Fall protection on steep pitched roofs. Regardless of the work activity, the employer must ensure that employees are protected from falling.	21	20	38	35	11	125
	296-880-20005(7)	WAC 296-880-20005 Fall protection required at four feet or more. (7) Fall protection on low pitched roofs. The employer must ensure that employees exposed to fall hazards are protected from falling.	5	6	17	12		40
	296-880-20005(9)	WAC 296-880-20005 Fall protection required at four feet or more. The employer must ensure that fall arrest systems, fall restraint systems, or positioning device systems are used.			2			2
	Total		54	78	153	117	19	421
880-100	296-880-10005(1)	WAC 296-880-10005 General requirements. (1) The employer must ensure that all surfaces on which employees will be working or walking on are structurally sound and will not collapse.				2		2
	296-880-10010(2)	WAC 296-880-10010 Fall protection required regardless of height. (2) The employer must guard holes into which an employee can trip, step into, or step through by a cover or other effective means.		4	1	1		6
	296-880-10010(3)	WAC 296-880-10010 Fall protection required regardless of height. (3) Regardless of height the employer must protect employees from falling into or onto impalement hazards.	7	5	8	8	1	29
	296-880-10015(1)	WAC 296-880-10015 Training. (1) Provide fall protection training for employees exposed to fall hazards. The employer must provide training for each employee exposed to fall hazards.				1		1
	296-880-10015(2)	WAC 296-880-10015 Training. (2) Each affected employee must be trained by a competent person to know at least the following: (a) The nature of fall hazards in the work area; (b) The use of fall protection equipment; (c) The use of fall protection systems.	1					1
	296-880-10020(1)	WAC 296-880-10020 Fall protection work plan required at ten feet or more. (1) The employer must develop and implement a written fall protection work plan including each of the following: (a) Identification of fall hazards; (b) Description of fall protection systems; (c) Training requirements; (d) Inspection and maintenance procedures; (e) Rescue procedures.	20	25	70	56	7	178
	296-880-10020(2)	WAC 296-880-10020 Fall protection work plan required at ten feet or more. (2) The fall protection work plan must: (a) Identify all fall hazards in the work area; (b) Describe the fall protection systems to be used; (c) Describe the training requirements for employees; (d) Describe the inspection and maintenance procedures for fall protection equipment; (e) Describe the rescue procedures for employees who become suspended or otherwise caught in fall protection equipment.	3	7	25	16	6	57
	296-880-10020(3)	WAC 296-880-10020 Fall protection work plan required at ten feet or more. (3) Prior to permitting employees into areas where fall hazards of ten feet or more exist the employer must ensure that the fall protection work plan is approved by a competent person.				2		2
	Total		31	41	104	86	14	276
880-300	296-880-30005(1)	WAC 296-880-30005 Construction work. This section applies to work activities under the scope of chapter 296-155 WAC, Safety standards for construction work, unless specifically exempted.		2	46			48
	296-880-30005(1)(a)	WAC 296-880-30005 Construction work. This section applies to work activities under the scope of chapter 296-155 WAC, Safety standards for construction work, unless specifically exempted.	21	24	3	31	6	85
	296-880-30005(1)(b)	WAC 296-880-30005 Construction work. This section applies to work activities under the scope of chapter 296-155 WAC, Safety standards for construction work, unless specifically exempted.	4	4	1	17	2	28
	296-880-30005(1)(c)	WAC 296-880-30005 Construction work. This section applies to work activities under the scope of chapter 296-155 WAC, Safety standards for construction work, unless specifically exempted.	4	7	3			14
	296-880-30005(2)(a)	WAC 296-880-30005 Construction work. This section applies to work activities under the scope of chapter 296-155 WAC, Safety standards for construction work, unless specifically exempted.			18	16	3	37
	296-880-30005(2)(b)(ii)(B)	WAC 296-880-30005 Construction work. This section applies to work activities under the scope of chapter 296-155 WAC, Safety standards for construction work, unless specifically exempted.			1			1
	296-880-30015(2)	WAC 296-880-30015 Elevating work platforms. (2) This subsection applies to vehicle mounted aerial devices. Before elevating the platform, the employer must ensure all personnel are properly trained.		1	1	2		4
	296-880-30015(4)	WAC 296-880-30015 Elevating work platforms. (4) This subsection applies to boom supported elevating work platforms. Before elevating the platform, the employer must ensure all personnel are properly trained.		2		6	1	9
	296-880-30030(1)	WAC 296-880-30030 Scaffolds. This section applies to suspended and supported scaffolds under the scope of chapter 296-874 WAC, Scaffolds. (1) The employer must protect employees from falling.	5	2	19	7		33
	296-880-30030(2)	WAC 296-880-30030 Scaffolds. This section applies to suspended and supported scaffolds under the scope of chapter 296-874 WAC, Scaffolds. (2) The employer must ensure that all surfaces on which employees will be working or walking on are structurally sound and will not collapse.				4		4
	296-880-30030(3)(b)	WAC 296-880-30030 Scaffolds. This section applies to suspended and supported scaffolds under the scope of chapter 296-874 WAC, Scaffolds. (3) Provide fall protection for employees on scaffolds.			3			3
	296-880-30030(5)(b)	WAC 296-880-30030 Scaffolds. This section applies to suspended and supported scaffolds under the scope of chapter 296-874 WAC, Scaffolds. (5) Provide fall protection if a scaffold is used.		1				1
	296-880-30030(6)(a)	WAC 296-880-30030 Scaffolds. This section applies to suspended and supported scaffolds under the scope of chapter 296-874 WAC, Scaffolds. (6) Provide specific types of fall protection for employees on scaffolds.			1			1
	296-880-30030(9)(b)	WAC 296-880-30030 Scaffolds. This section applies to suspended and supported scaffolds under the scope of chapter 296-874 WAC, Scaffolds. (9) Ensure vertical lifelines are used.		2				2
	Total		34	45	100	79	12	270
876-400	296-876-40005(1)	WAC 296-876-40005 Designed use. (1) You must use ladders only for their intended purpose. Note: Unless specifically recommended by the manufacturer, do not use a ladder on a surface that is not designed to be used as a ladder.		1	1	2		4
	296-876-40005(2)	WAC 296-876-40005 Designed use. (2) You must make sure not to overload ladders. Do not exceed either the: (a) Maximum intended load; or (b) Manufacturer's rated capacity.				1		1
	296-876-40015(1)	WAC 296-876-40015 Support. (1) You must place the ladder either: (a) With a secure footing on a firm, level support surface; or (b) Secure the ladder to prevent accidental movement.	2	3	4	4	2	15
	296-876-40015(4)	WAC 296-876-40015 Support. (4) You must place a straight ladder so the side rails are equally supported by the top support, unless the ladder is equipped with a single support.				2		2
	296-876-40020(1)	WAC 296-876-40020 Set-up. (1) You must set up non-self-supporting ladders at a safe angle. The ladder is set at the proper angle when the horizontal distance from the top support to the base of the ladder is equal to the working length of the ladder.	2	3	4	2	1	12
	296-876-40025(6)	WAC 296-876-40025 Climbing and descending. (6) You must make sure no employee carries any object or load that could cause the employee to lose balance and fall while climbing or descending.	3	1	3	1		8
	296-876-40030(1)	WAC 296-876-40030 Getting on and off ladders at upper levels. (1) You must make sure a ladder used to access an upper level has the side rails extended at least 3 feet (0.9 m) above and below the upper level.	11	22	47	39	6	125
	296-876-40030(2)	WAC 296-876-40030 Getting on and off ladders at upper levels. (2) You must do the following if a ladder used to access an upper level is not long enough to obtain a three-foot overlap: (a) Use a ladder with a built-in three-foot overlap; or (b) Use a ladder with a built-in three-foot overlap.		1	6		1	8
	296-876-40040(2)	WAC 296-876-40040 Persons on ladders. (2) You must secure the ladder at the top and bottom when working from it.				1	3	4
	296-876-40045(1)	WAC 296-876-40045 Multisection ladders. (1) You must make sure not to tie or fasten ladder sections together to make longer ladders unless: (a) The ladder manufacturer specifically allows it; or (b) The ladder is designed to be used as a longer ladder.				1		1
	296-876-40050(1)	WAC 296-876-40050 Self-supporting ladders. (1) You must make sure self-supporting ladders are not used as single ladders or in the partially closed position.	2		12	8	2	24
	296-876-40050(2)	WAC 296-876-40050 Self-supporting ladders. (2) You must make sure stepladders are fully opened with the spreaders locked.			1			1
	296-876-40050(3)	WAC 296-876-40050 Self-supporting ladders. (3) You must make sure not to climb on the rear braces of a self-supporting ladder unless they are designed and recommended for that use.				1		1
	296-876-40050(4)(a)	WAC 296-876-40050 Self-supporting ladders. (4) You must prohibit standing or stepping on the: (a) Top cap and top step of a step or trestle ladder. EXEMPTION: The restraint system is used.	1	4	14	15	2	36

Stute Violation Details CY 2021 - 2025TD

WAC Chapter Section	WAC Cited	WAC Text	2021	2022	2023	2024	2025	Totals
			Vios	Vios	Vios	Vios	Vios	
	Total		21	35	94	78	14	242
155-350	296-155-350(1)	WAC 296-155-350 General requirements. (1) Condition of tools. All hand and power tools and similar equipment, whether furnished by the employer or the employee, shall				1		1
	296-155-350(2)(a)	WAC 296-155-350 General requirements. (2) Guarding. (a) When power operated tools are designed to accommodate guards, they shall be equipped with such guards wh		1				1
	296-155-350(3)	WAC 296-155-350 General requirements. (3) Personal protective equipment. Employees using hand and power tools and exposed to the hazard of falling, flying, abrasive, &	24	20	53	49	6	152
	Total		24	21	53	50	6	154
155-655	296-155-655(10)(a)	WAC 296-155-655 General protection requirements. (10) Protection of employees from loose rock or soil. (a) Adequate protection shall be provided to protect employees fro			1			1
	296-155-655(10)(b)	WAC 296-155-655 General protection requirements. (10) Protection of employees from loose rock or soil. (b) You must protect employees from excavated or other materia		3	7	7	1	18
	296-155-655(11)(a)	WAC 296-155-655 General protection requirements. (11) Inspections. (a) Daily inspections of excavations, the adjacent areas, and protective systems shall be made by a coi		4	6	8	3	21
	296-155-655(11)(b)	WAC 296-155-655 General protection requirements. (11) Inspections. (b) Where the competent person finds evidence of a situation that could result in a possible cave-in, ind		1	2	5		8
	296-155-655(12)(a)	WAC 296-155-655 General protection requirements. (12) Fall protection. (a) You must provide walkways where employees or equipment are required or permitted to cross					1	1
	296-155-655(2)(a)	WAC 296-155-655 General protection requirements. (2) Underground installations. (a) The location of utility installations, such as sewer, telephone, fuel, electric, water lines,					1	1
	296-155-655(2)(c)	WAC 296-155-655 General protection requirements. (2) Underground installations. (c) When excavation operations approach the location of underground installations				1		1
	296-155-655(3)(b)	WAC 296-155-655 General protection requirements. (3) Access and egress. (b) Means of egress from trench excavations. A stairway, ladder, ramp or other safe means of eg		5	9	6	2	22
	296-155-655(8)(b)	WAC 296-155-655 General protection requirements. (8) Protection from hazards associated with water accumulation. (b) If water is controlled or prevented from accumulati					2	2
	296-155-655(9)(c)	WAC 296-155-655 General protection requirements. (9) Stability of adjacent structures. (c) Sidewalks, pavements, and appurtenant structure shall not be undermined unless			1	1		2
	Total			13	26	28	10	77
874-200	296-874-20002(1)	WAC 296-874-20002 Make sure scaffolds are properly designed and constructed. (1) You must make sure scaffolds are: (a) Designed by a qualified person; and (b) Constr	1	1	3	4		9
	296-874-20002(2)	WAC 296-874-20002 Make sure scaffolds are properly designed and constructed. (2) You must prohibit the use of shore and lean-to scaffolds.			1			1
	296-874-20004	WAC 296-874-20004 Make sure scaffolds are erected, moved, altered, or dismantled by qualified persons. You must make sure scaffolds are erected, moved, altered, or dism			2			2
	296-874-20006(1)(b)	WAC 296-874-20006 Maintain structural integrity when intermixing scaffold components. (1) You must make sure intermixed scaffold components: (b) Maintain the scaffold	3			1		4
	296-874-20008(1)	WAC 296-874-20008 Make sure platforms are properly planked or decked. (1) You must fully plank or deck each platform between the front uprights and the guardrail suppo			4			4
	296-874-20010	WAC 296-874-20010 Make sure platforms meet minimum width requirements. You must make sure scaffold platforms meet the minimum width requirements of Table 1,	2		2	3		7
	296-874-20012(1)	WAC 296-874-20012 Meet these requirements when using shorter platforms to create a longer platform. (1) You must make sure, when platforms are overlapped to create a			1			1
	296-874-20016(1)	WAC 296-874-20016 Stabilize the ends of platforms. (1) You must make sure each end of a platform: (a) Is cleated or restrained by hooks or equivalent means; or (b) Exte			3	3		6
	296-874-20016(2)	WAC 296-874-20016 Stabilize the ends of platforms. (2) You must make sure the cantilevered portion of a platform meets at least one of the following: (a) Is designed and	2		1	1	1	5
	296-874-20018	WAC 296-874-20018 Keep platform sag within acceptable limits. You must make sure a loaded platform does not sag more than one-sixtieth of the span.			1			1
	296-874-20020(1)	WAC 296-874-20020 Provide safe access to scaffolds. (1) You must provide scaffold platforms more than two feet (0.6 m) above or below a point of access with at least one o		1	1			2
	296-874-20032	WAC 296-874-20032 Make sure surfaces used to access scaffolds are close enough to use safely. You must make sure a surface used to provide access to or from a scaffold is			2			2
	296-874-20034	WAC 296-874-20034 Inspect scaffolds and scaffold components. You must make sure scaffolds and scaffold components are inspected for visible defects by a competent pers	1	2	1			4
	296-874-20042(2)(e)	WAC 296-874-20042 Increase employee working level height on scaffolds safely. (2) You must meet all of the following when using stilts on scaffolds: (e) Meet all of the foll			1			1
	296-874-20046	WAC 296-874-20046 Protect employees from energized power lines. You must make sure scaffolds are erected, moved, altered, or dismantled so that they, and any condu	2	1	1	2		6
	296-874-20066(1)	WAC 296-874-20066 Provide falling object protection. Reference: Hardhats and possibly other personal protective equipment has to be used to protect employees exposed		1	4	1		6
296-874-20072(2)	WAC 296-874-20072 Train employees who work on a scaffold. (2) You must include the following subjects in your training: (a) Hazards in the work area and how to deal wit			1			1	
	Total		11	6	29	15	1	62
874-400	296-874-40006(2)	WAC 296-874-40006 Make sure supported scaffolds are properly supported. (2) You must make sure supported scaffold poles, legs, posts, frames, and uprights, bear on base		1		5		6
	296-874-40006(5)	WAC 296-874-40006 Make sure supported scaffolds are properly supported. (5) You must make sure mobile scaffolds meet these additional requirements: (a) Wheel and c			2		2	
	296-874-40008(1)	WAC 296-874-40008 Provide safe access for persons erecting or dismantling supported scaffolds. (1) You must provide a safe means of access for persons erecting or disman			1			1
	296-874-40018(2)	WAC 296-874-40018 Meet these requirements when using fabricated frame scaffolds (tubular welded frame scaffolds). (2) You must brace frames and panels using crossbrac			1			1
	296-874-40026(4)	WAC 296-874-40026 Meet these requirements when using ladder jack scaffolds. (4) You must make sure ladders used to support ladder jacks are: (a) Type I (two hundred fi			1			1
	296-874-40032(1)	WAC 296-874-40032 Meet these requirements when using pump jack scaffolds. (1) You must make sure pump jack brackets, braces, and accessories are made from metal pl			1			1
	296-874-40032(3)	WAC 296-874-40032 Meet these requirements when using pump jack scaffolds. (3) You must secure poles to the structure using rigid triangular bracing or the equivalent loca	8	6	19	9	2	44
	296-874-40038(1)	WAC 296-874-40038 Meet these requirements when using step, platform and trestle ladder scaffolds. (1) You must make sure ladders used to support step, platform, and tr				4		4
	296-874-40038(3)	WAC 296-874-40038 Meet these requirements when using step, platform and trestle ladder scaffolds. (3) You must make sure scaffold platforms are not placed higher than t				2		2
		Total		8	7	25	20	2
155-477	296-155-477(1)(c)	WAC 296-155-477 Stairways. (1) General. The following requirements apply to all stairways as indicated: (c) In all buildings or structures two or more stories or twenty-four	2		1	1		4
	296-155-477(1)(d)	WAC 296-155-477 Stairways. (1) General. The following requirements apply to all stairways as indicated: (d) Stairways, ramps or ladders shall be provided at all points wher			1	2		3
	296-155-477(1)(f)	WAC 296-155-477 Stairways. (1) General. The following requirements apply to all stairways as indicated: (f) Wood frame buildings.				1		1
	296-155-477(1)(f)(i)	WAC 296-155-477 Stairways. (1) General. The following requirements apply to all stairways as indicated: (f) Wood frame buildings. (i) The stairway to a second or higher f	2	7	4	6	2	21
296-155-477(3)(a)	WAC 296-155-477 Stairways. (3) Stairrails and handrails. The following requirements apply to all stairways as indicated: (a) Stairways having four or more risers or rising r	3	5	9	3		20	

Stute Violation Details CY 2021 - 2025TD

WAC Chapter Section	WAC Cited	WAC Text	2021	2022	2023	2024	2025	Totals
			Vios	Vios	Vios	Vios	Vios	
	296-155-477(3)(a)(i)	WAC 296-155-477 Stairways. (3) Stairrails and handrails. The following requirements apply to all stairways as indicated: (a) Stairways having four or more risers or rising more		1	2		1	4
	296-155-477(3)(a)(ii)	WAC 296-155-477 Stairways. (3) Stairrails and handrails. The following requirements apply to all stairways as indicated: (a) Stairways having four or more risers or rising more			1	1	1	3
	296-155-477(3)(d)	WAC 296-155-477 Stairways. (3) Stairrails and handrails. The following requirements apply to all stairways as indicated: (d) Midrails, screens, mesh, intermediate vertical m			3			3
	296-155-477(3)(l)	WAC 296-155-477 Stairways. (3) Stairrails and handrails. The following requirements apply to all stairways as indicated: (l) You must provide unprotected sides and edges		1				1
	Total		7	13	22	14	4	60
155-657	296-155-657(1)(a)	WAC 296-155-657 Requirements for protective systems. (1) Protection of employees in excavations. (a) You must protect each employee in an excavation from cave-ins by	2	8	13	19	5	47
	296-155-657(1)(a)(ii)	WAC 296-155-657 Requirements for protective systems. (1) Protection of employees in excavations. (a) Each employee in an excavation shall be protected from cave-ins by ai			1			1
	296-155-657(3)(b)(iii)	WAC 296-155-657 Requirements for protective systems. (3) Design of support systems, shield systems, and other protective systems. Designs of support systems, shield syste			1			1
	296-155-657(4)(b)	WAC 296-155-657 Requirements for protective systems. (4) Materials and equipment. (b) You must use and maintain manufactured materials and equipment used for prot			1			1
	296-155-657(5)(a)(ii)	WAC 296-155-657 Requirements for protective systems. (5) Installation and removal of support. (a) General. (ii) You must install and remove support systems in a mann				1		1
	296-155-657(7)(a)(iii)	WAC 296-155-657 Requirements for protective systems. (7) Shield systems. (a) General. (iii) You must protect employees from the hazard of cave-ins when entering or ex				1		1
	Total		2	8	16	21	5	52
155-205	296-155-205(1)(a)	WAC 296-155-205 Head protection. (1) All employees on any construction site shall be provided an individual hard hat which meets all requirements of (a)through (c) of this				2		2
	296-155-205(3)	WAC 296-155-205 Head protection. (3) All employees shall wear a hard hat on any construction site whenever there is a potential exposure to danger of flying or falling obji	9	7	24	7	2	49
	Total		9	7	24	9	2	51
155-680	296-155-680(10)(a)	WAC 296-155-680 General provisions. (10) Impalement protection and custody. (a) You must guard all protruding reinforcing steel, onto and into which employees could fal	4	8	10	14	1	37
	Total		4	8	10	14	1	37
155-305	296-155-305(1)(a)	WAC 296-155-305 Signaling and flaggers. (1) General requirements for signaling and flaggers. (a) Employers must first apply the requirements in this section. Then yc			6	2		8
	296-155-305(3)(a)	WAC 296-155-305 Signaling and flaggers. Definition: Flagger means a person who provides temporary traffic control. For the purposes of this chapter, MUTCD r			3	3		6
	296-155-305(4)	WAC 296-155-305 Signaling and flaggers. Definition: Flagger means a person who provides temporary traffic control. For the purposes of this chapter, MUTCD r			2			2
	296-155-305(5)	WAC 296-155-305 Signaling and flaggers. Definition: Flagger means a person who provides temporary traffic control. For the purposes of this chapter, MUTCD means the Fe				2		2
	296-155-305(5)(a)	WAC 296-155-305 Signaling and flaggers. Definition: Flagger means a person who provides temporary traffic control. For the purposes of this chapter, MUTCD r				1		1
	296-155-305(7)(a)	WAC 296-155-305 Signaling and flaggers. Definition: Flagger means a person who provides temporary traffic control. For the purposes of this chapter, MUTCD r			1			1
	296-155-305(7)(b)	WAC 296-155-305 Signaling and flaggers. Definition: Flagger means a person who provides temporary traffic control. For the purposes of this chapter, MUTCD r			1	1		2
	296-155-305(8)(a)	WAC 296-155-305 Signaling and flaggers. Definition: Flagger means a person who provides temporary traffic control. For the purposes of this chapter, MUTCD means the Fe			3	5		8
	296-155-305(8)(c)	WAC 296-155-305 Signaling and flaggers. Definition: Flagger means a person who provides temporary traffic control. For the purposes of this chapter, MUTCD means the Fe			1			1
	296-155-305(9)(b)	WAC 296-155-305 Signaling and flaggers. Definition: Flagger means a person who provides temporary traffic control. For the purposes of this chapter, MUTCD r				2		2
	Total				17	16		33
869-600	296-869-60005	WAC 296-869-60005 Intended use. You must make sure elevating work platforms are used only for their intended purpose as specified by the manufacturer. Note: Misus		1	1	1		3
	296-869-60010	WAC 296-869-60010 Workplace survey. You must have the operator survey the area before and during use of an elevating work platform for hazards such as: (1) Drop-offs		1				1
	296-869-60030(1)	WAC 296-869-60030 Driving. Important: This section does not apply to manually propelled elevating work platforms. (1) You must make sure the operator does all of the		3				3
	296-869-60035(1)	WAC 296-869-60035 Elevating and lowering the platform. (1) You must have the operator make sure all of the following are done before each elevation of the platform: (a)				2		2
	296-869-60040(1)	WAC 296-869-60040 Working from the platform. (1) You must make sure persons working from the platform: (a) Keep a firm footing on the platform; and (b) Do not use			4	2		6
	296-869-60040(2)	WAC 296-869-60040 Working from the platform. (2) You must make sure all persons on the platform of boom-supported elevating work platforms wear a full body harness a	1	2	2	2		7
	296-869-60040(3)	WAC 296-869-60040 Working from the platform. (3) You must make sure the rated capacities of the platform are not exceeded when transferring loads to the platform at ar	1					1
	Total		2	7	7	7		23
155-215	296-155-215(1)(a)	WAC 296-155-215 Eye and face protection. (1) General. (a) Employees shall use eye and face protection equipment when machines or operations present potential eye or	5	4	6	5		20
	Total		5	4	6	5		20
863-400	296-863-40005(1)	WAC 296-863-40005 Protect employees around PITs. (1) You must make sure operators use restraint devices, such as seatbelts or lap-bars, when they are provided on the PIT		1		1		2
	296-863-40005(4)	WAC 296-863-40005 Protect employees around PITs. (4) You must make sure people riding on PITs have a safe place to ride.				1		1
	296-863-40010(1)	WAC 296-863-40010 Operate PITs safely. (1) You must operate PITs according to the manufacturer's instructions.	2					2
	296-863-40020(1)(a)	WAC 296-863-40020 Meet these requirements when the operator leaves the normal operating position. (1) You must make sure operators do the following when getting off i				1		1
	296-863-40020(2)(a)	WAC 296-863-40020 Meet these requirements when the operator leaves the normal operating position. (2) Make sure operators do the following when leaving a PIT unatten		2	3	1		6
	296-863-40060(1)(a)	WAC 296-863-40060 Make sure work platforms and PITs used to lift people meet these requirements. (1) You must make sure work platforms: (a) Are securely fastened to		1				1
	296-863-40060(1)(b)	WAC 296-863-40060 Make sure work platforms and PITs used to lift people meet these requirements. (1) You must make sure work platforms: (b) Have standard guardrails		2		1		3
	296-863-40060(2)	WAC 296-863-40060 Make sure work platforms and PITs used to lift people meet these requirements. (2) You must guard the area between the platform and the PIT mast to		1				1
	296-863-40065(2)	WAC 296-863-40065 Operate PITs using elevated work platforms safely. (2) You must make sure the operator does not move the PIT from one point to another while work:				1		1
	Total		2	7	3	6		18
880-400	296-880-40005(1)	WAC 296-880-40005 Guardrail systems. Guardrail systems and their use must conform to the following provisions: (1) A standard guardrail system must consist of top rail, i			6	3		9

Stute Violation Details CY 2021 - 2025TD

WAC Chapter Section	WAC Cited	WAC Text	2021	2022	2023	2024	2025	Totals
			Vios	Vios	Vios	Vios	Vios	
	296-880-40015(1)(b)	WAC 296-880-40015 Cover Requirements - Holes and openings. Covers and their use must conform to the following provisions: (1) Hole covers must be of any material tha		3				3
	Total			3	6	3		12
869-200	296-869-20045(1)	WAC 296-869-20045 Working from the platform. (1) You must make sure boom and platform load limits specified by the manufacturer are not exceeded.			1			1
	296-869-20045(2)	WAC 296-869-20045 Working from the platform. (2) You must make sure persons stand firmly on the floor of the platform and do not: (a) Sit or climb on the edge of the pl				2	1	3
	296-869-20045(4)	WAC 296-869-20045 Working from the platform. (4) You must make sure all persons on the platform wear a full body harness with a lanyard attached to either: (a) The ma		1	4		1	6
	Total			1	5	2	2	10
876-300	296-876-30005(1)	WAC 296-876-30005 Condition and inspection. (1) You must keep portable ladders in good, usable condition. Good, usable condition includes, but is not limited to: (a) Joint:		2	5	3		10
	Total			2	5	3		10
155-40	296-155-040(1)	WAC 296-155-040 Safe place standards. (1) Each employer shall furnish to each employee a place of employment free from recognized hazards that are causing or likely to c	2	1		1		4
	296-155-040(2)	WAC 296-155-040 Safe place standards. (2) Every employer shall require safety devices, furnish safeguards, and shall adopt and use practices, methods, operations, and prc			1	2		3
	Total		2	1	1	3		7
155-110	296-155-110(2)	WAC 296-155-110 Accident prevention program. (2) You must develop a formal accident-prevention program, tailored to the needs of the particular plant or operation and	2		1	1	1	5
	296-155-110(9)(a)	WAC 296-155-110 Accident prevention program. (9) Every employer shall conduct walk-around safety inspections as follows: (a) At the beginning of each job, and at lea				1		1
	Total		2		1	2	1	6
155-20	296-155-020(10)	WAC 296-155-020 Housekeeping. (10) During the course of construction, alteration, repair or demolition of buildings and structures, employers shall ensure continuous clean		1				1
	296-155-020(12)	WAC 296-155-020 Housekeeping. (12) All floors and walkways shall be maintained in good condition. Loose or broken components shall be repaired or replaced. Secure foo		1				1
	296-155-020(2)	WAC 296-155-020 Housekeeping. (2) To facilitate cleaning, every floor, working surface, and passageway shall be kept free from protruding nails, splinters, loose boards or o			1			1
	296-155-020(4)	WAC 296-155-020 Housekeeping. (4) In areas where workers may pass or perform duties, all debris and accumulations of material shall be removed. Hoses and electrical cor			1			1
	296-155-020(6)	WAC 296-155-020 Housekeeping. (6) Storage of material shall not create a hazard. Bags, containers, bundles, construction materials and other equipment shall be stored in ti		1				1
	Total			3	2			5
155-615	296-155-615(1)(b)	WAC 296-155-615 Material handling equipment. (1) General requirements for earthmoving equipment. (b) Seat belts. • Seat belts must be provided and used by all ope					1	1
	296-155-615(1)(c)	WAC 296-155-615 Material handling equipment. (1) General requirements for earthmoving equipment. (c) Access roadways and grades. • Equipment must not			1			1
	296-155-615(3)(b)	WAC 296-155-615 Material handling equipment. (3) Lifting and hauling equipment (other than equipment covered under Part L of this chapter). Industrial trucks (including for	1					1
	296-155-615(3)(h)	WAC 296-155-615 Material handling equipment. (3) Lifting and hauling equipment (other than equipment covered under Part L of this chapter). Industrial trucks (includi			1		1	2
	Total		1		2		2	5
155-476	296-155-476(1)	WAC 296-155-476 General requirements. (1) A stairway or ladder shall be provided at all personnel points of access where there is a break in elevation of 19 inches (48 cm) o			3	1		4
	Total				3	1		4
155-370	296-155-370(2)	WAC 296-155-370 Woodworking tools. (2) Guarding. All portable, hand held power-driven circular saws shall be equipped with guards above and below the base plate or sh				1		1
	296-155-370(3)(a)	WAC 296-155-370 Woodworking tools. (3) Hand-fed table saws. (a) Each circular hand-fed table saw shall be provided with a hood-type guard that will cover the blade at al				1		1
	296-155-370(3)(e)	WAC 296-155-370 Woodworking tools. (3) Hand-fed table saws. (e) Where a hood-type guard cannot be used because of unusual shapes or cuts, a jig or fixture that will pro			1			1
	Total				1	2		3
807-140	296-807-14005	WAC 296-807-14005 Follow the manufacturer's instructions. You must follow the manufacturer's instructions for safe use of the tool.				1		1
	296-807-14035(3)	WAC 296-807-14035 Use air tools safely. Exemption: This section does not apply to: 1. Tools specifically for medical or dental use; 2. Tools specifically for use in the food	2					2
	Total		2			1		3
155-428	296-155-428(1)(e)	WAC 296-155-428 General requirements. (1) Protection of employees. (e) No work shall be performed, no material shall be piled, stored or otherwise handled, no scaffolding,				2		2
	296-155-428(1)(g)(ii)	WAC 296-155-428 General requirements. (1) Protection of employees. (g) Overhead electric lines. Where overhead electric conductors are encountered in proximity to a worl	1					1
	Total		1			2		3
155-533	296-155-53306(1)	WAC 296-155-53306 Rigger Qualifications. (1) The rigger must meet the qualification requirements (subsection (3) of this section) prior to performing hoisting activities for as			2			2
	Total				2			2
155-337	296-155-33705(2)	WAC 296-155-33705 General requirements. (2) All slings in use must meet the applicable requirements for design, inspection, construction, testing, maintenance and operati				1		1
	296-155-33705(4)	WAC 296-155-33705 General requirements. (4) All rigging gear must be used in accordance with the manufacturer's recommendations or a qualified person.				1		1
	Total					2		2
806-480	296-806-48012	WAC 296-806-48012 Safeguard hand-fed circular table saws. (1) You must guard each hand-fed circular saw with a hood that completely encloses both the portion of the sav			2			2
	Total				2			2
155-367	296-155-367(4)(a)	WAC 296-155-367 Masonry saws. (4) Exhaust and eye protection. (a) All table mounted masonry saws shall be equipped with a mechanical means of exhausting dust into a co		1				1
	296-155-367(4)(b)	WAC 296-155-367 Masonry saws. (4) Exhaust and eye protection. (b) All portable hand-held masonry saw operators shall wear appropriate eye and respiratory protection ir		1				1
	Total			2				2
809-200	296-809-20002	WAC 296-809-20002 Identify permit-required confined spaces. You must identify all permit-required confined spaces in your workplace. Use a person with the knowledge, sk				1		1
	296-809-20004(2)	WAC 296-809-20004 Inform employees and control entry to permit-required confined spaces. (2) You must take effective measures to prevent unauthorized employees from				1		1

Stute Violation Details CY 2021 - 2025TD

WAC Chapter Section	WAC Cited	WAC Text	2021	2022	2023	2024	2025	Totals
			Vios	Vios	Vios	Vios	Vios	
	Total					2		2
840-105	296-840-105(2)	WAC 296-840-105 Exposure assessment. This section applies to all occupational exposures except for tasks performed according to the requirements in WAC 296-840-110.		1			1	2
	Total			1			1	2
863-200	296-863-20010(1)(b)	WAC 296-863-20010 Meet these requirements when modifying or altering PITs. (1) You must have written approval from the PIT manufacturer before making any modificati				1	1	2
	Total					1	1	2
155-35	296-155-035(8)	WAC 296-155-035 General requirements. (8) As construction progresses, the component parts of structures shall be secured or braced to prevent collapse or failure.		2				2
	Total			2				2
155-235	296-155-235(3)	WAC 296-155-235 Working over or adjacent to water. (3) Ring buoys with at least 90 feet of line shall be provided and readily available for emergency rescue operations. Di		1				1
	296-155-235(4)	WAC 296-155-235 Working over or adjacent to water. (4) At least one lifesaving skiff shall be immediately available at locations where employees are working over or adjace		1				1
	Total			2				2
800-160	296-800-16050	WAC 296-800-16050 Make sure your employees use appropriate eye and face protection. (1) You must make sure that employees exposed to hazards that could injure their r			1			1
	296-800-16050(1)	WAC 296-800-16050 Make sure your employees use appropriate eye and face protection. (1) You must make sure that employees exposed to hazards that could injure their r				1		1
	Total				1	1		2
155-771	296-155-77100(3)(d)	WAC 296-155-77100 Hoists, elevators, excavators, and conveyors. (3) Excavation machines. (d) All persons must keep away from the range of the shovel's swing and must n			1			1
	296-155-77100(3)(m)	WAC 296-155-77100 Hoists, elevators, excavators, and conveyors. (3) Excavation machines. (m) You must not leave tools on the cab floor. You must not store spare cans of			1			1
	Total				2			2
155-338	296-155-33820(6)(a)(iv)	WAC 296-155-33820 Synthetic webbing slings. (6) Use of synthetic webbing slings. (a) Use synthetic webbing slings safely by meeting all of the following requirements:	2					2
	Total		2					2
155-120	296-155-120(1)	WAC 296-155-120 First-aid training and certification. This section is designed to assure that all employees in this state are afforded quick and effective first-aid attention in th			1			1
	296-155-120(2)	WAC 296-155-120 First-aid training and certification. This section is designed to assure that all employees in this state are afforded quick and effective first-aid attention in th				1		1
	Total				1	1		2
800-150	296-800-15030	WAC 296-800-15030 Make sure emergency washing facilities are functional and readily accessible. (1) You must provide an emergency shower: (a) When there is potential			1			1
	296-800-15035	WAC 296-800-15035 Inspect and activate your emergency washing facilities. (1) You must make sure all plumbed emergency washing facilities are inspected once a year to r				1		1
	Total				1	1		2
863-600	296-863-60005(1)(a)	WAC 296-863-60005 Make sure PIT operators are trained. (1) You must make sure employees successfully complete an operator training program before operating PITs. The				1		1
	Total					1		1
840-140	296-840-140(1)	WAC 296-840-140 Written exposure control plan. (1) You must establish and implement a written exposure control plan that contains at least the following elements: (a)		1				1
	Total			1				1
840-110	296-840-110(2)(b)	WAC 296-840-110 Specified exposure control methods. This section applies to construction work and other occupational exposures where the task performed is indistinguish		1				1
	Total			1				1
155-375	296-155-375(1)	WAC 296-155-375 Jacks — Lever and ratchet, screw, and hydraulic. General requirements. (1) The manufacturer's rated capacity shall be legibly marked on all jacks an		1				1
	Total			1				1
155-100	296-155-100(1)(c)	WAC 296-155-100 Management's responsibility. (1) It shall be the responsibility of management to establish, supervise, and enforce, in a manner which is effective in practic				1		1
	Total					1		1
155-360	296-155-360(2)(b)	WAC 296-155-360 Power-operated hand tools. (2) Pneumatic power tools. (b) Safety clips or retainers shall be securely installed and maintained on pneumatic imp		1				1
	Total			1				1
842-130	296-842-13005	WAC 296-842-13005 Select and provide appropriate respirators. A respirator must be provided to each employee when such equipment is necessary to protect the health of			1			1
	Total				1			1
840-150	296-840-150(3)	WAC 296-840-150 Communication of respirable crystalline silica hazards to employees. (3) Regarding employee information and training, you must ensure that each employ	1					1
	Total		1					1
27-1101	296-27-01101(1)	WAC 296-27-01101 Recording criteria. (1) Employers required to keep records by this chapter must record each fatality, injury and illness that: (a) Is work-related, see WA		1				1
	Total			1				1
840-120	296-840-120(1)	WAC 296-840-120 Methods of compliance. This section does not apply to tasks listed and performed in accordance with Table 1 of WAC 296-840-110 Specified exposure con	1					1
	Total		1					1
155-325	296-155-325(2)(h)(ii)	WAC 296-155-325 General requirements for storage. (2) Material storage. (h) Lumber: (ii) Lumber shall be stacked on level and solidly supported sills.		1				1
	Total			1				1
155-200	296-155-200(1)(d)	WAC 296-155-200 General requirements for personal protective equipment (PPE). (1) Supplying personal protective equipment (d) All personal protective equipment mu			1			1
	Total				1			1
842-180	296-842-18005(2)	WAC 296-842-18005 Prevent sealing problems with tight-fitting respirators. (2) Make sure you do NOT permit respirator use if employees have a characteristic that interfe			1			1

Stute Violation Details CY 2021 - 2025TD

WAC Chapter Section	WAC Cited	WAC Text	2021	2022	2023	2024	2025	Totals
			Vios	Vios	Vios	Vios	Vios	
	Total				1			1
155-210	296-155-210	WAC 296-155-210 Hearing protection. The hearing protection requirements of the general occupational health standards, chapter 296-62 WAC, shall apply.		1				1
	Total			1				1
155-775	296-155-775(13)(b)	WAC 296-155-775 Preparatory operations. (13) Cover requirement - Holes. (b) You must mark each cover with the word "hole" or "cover" to provide warning of the hazard.			1			1
	Total				1			1
155-211	296-155-211	WAC 296-155-211 Leg protection. Employees whose duties require them to operate a power chain saw shall wear flexible ballistic nylon pads, sewn or otherwise fastened i		1				1
	Total			1				1
807-180	296-807-18035	WAC 296-807-18035 Use side handles on vertical and angle grinders. You must use a side handle on all four-inch and larger vertical and angle grinders.					1	1
	Total						1	1
155-140	296-155-140(2)(a)	WAC 296-155-140 Sanitation. (2) Wash water. (a) Clean, tepid wash water, between 70 and 100 degrees Fahrenheit, shall be provided at all construction sites.			1			1
	Total				1			1
809-400	296-809-40002(2)	WAC 296-809-40002 Provide employee training. (2) You must provide training to each affected employee; (a) Before an employee is first assigned to duties covered by this				1		1
	Total					1		1
62-077	296-62-07721(2)(e)	WAC 296-62-07721 Communication of hazards. (2) Communication of hazards to employees. Requirements for construction and shipyard employment activities. (e) No co			1			1
	Total				1			1
155-335	296-155-335(2)	WAC 296-155-335 Disposal of waste materials. (2) When debris is dropped without the use of chutes, the area onto which the material is dropped shall be completely enclos		1				1
	Total			1				1
155-558	296-155-55820(2)(b)	WAC 296-155-55820 Synthetic webbing slings. (2) Inspection. (b) A qualified person must perform a visual inspection for damage, each day or shift the synthetic webbing sling					1	1
	Total						1	1
876-150	296-876-15005(1)	WAC 296-876-15005 Training. (1) You must train employees to recognize ladder hazards and the procedures to minimize these hazards.		1				1
	Total			1				1
155-415	296-155-415(2)(a)	WAC 296-155-415 Ventilation and protection in welding, cutting, and heating. (2) Welding, cutting, and heating in confined spaces. (a) Except as provided in subdivision (b			1			1
	Total				1			1
			226	327	731	595	99	1,978